


Security Light

30 W / 35 W

OB150Nc



Beam Angle : 330°



OB150Nsc : E26/27 Socket OB150Nlc : E39/40 Socket




DIMENSION

OB150Nsc

- Size : ϕ 71 x 150 mm
- Weight : 205 g

OB150Nlc

- Size : ϕ 71 x 150 mm
- Weight : 220 g



FEATURES

- LED replacement for 70~100W Metal Halide lamp
- Ultra-high efficacy of 150 lm/W
- Ideal for outdoor security light
- Super light and compact design for easy installation and safety
- Clear type cover enables greater brightness
- Mesh application to prevent the inflow of foreign substances
- Optimized heat dissipation with fan circulation system
- Ultraviolet free, no mercury and lead-free RoHS Compliance

SPECIFICATION

Model No.	Wattage	Replacement	Luminous Efficacy	Total Lumen	CRI	CCT	Voltage	Frequency
OB150Nsc-30W	30 W	MH 70-100 W	150 lm/W	4,500 lm	80 Ra	5,700 K	AC 100-240 V	50/60 Hz
OB150Nlc-30W								
OB150Nsc-35W	35 W			5,250 lm				
OB150Nlc-35W								

- PF : > 0.96
- THD : < 15 %
- Material : PA6

- Socket : E26/27 , E39/40
- Operating Temperature : -20°C ~ 50°C (-4°F ~ 122°F)
- Installation Angle : 360°

- CCT : Standard - 5700 K, 3000 K / Option - 5000 K, 4000 K, 2700 K

- LED Package Life time : 50,000 hours (25°C)

*LED package life time according to industry standard (LM80), high operating temperature may shorten life span of LED package and LED lamp.

APPLICATION



Park



Walkway



Residential Area



Outdoor Parking Lot

LED HIGH BAY

LED FLOOD LIGHT

LED BULB

OB150N / OB150Nc / OB200 / OB200c / OB230 / OB230c



Mesh Structure

*Illustrated by : OB200c

Mesh application to prevent the inflow of foreign substances



LIGHTING FIXTURE

① Recommended



Cutoff streetlight



Fully shieldedtype



Fully shieldedtype



Fully shieldedtype



Downward type




Horizontal light fixture

② Unsuitable



Small fixture



Unshielded Shade



Downlight