

LED 투광등 HB2000-80T



제품 사양

• 전기적 특성


정격전력	80 W
정격전압	AC 120 - 277 V
정격주파수	60 Hz
역률(PF)	> 0.9
THD	< 15%
서지보호	L-L (4KV), L-FG (6KV)

• 구조적 특성

규격	ø 276 x 277 mm
무게	2.7 kg
몸체 재질	PA6+GF30%
히트싱크	ALDC12
IP 등급	IP66
작동 온도	-30°C ~ 50°C (-22°F ~ 122°F)
설치 각도	360°

• 광학적 특성

총광량	12,000 lm
광효율	150 lm/W
대체출력	MH 250 W
색온도	5,700 K
LED 칩 정격수명	50,000 시간 (상온 25°C 기준) *LED 칩 수명과 제품 수명은 차이가 있습니다. *사용 온도가 높을 경우 수명이 짧아질 수 있습니다.
연색지수	80 Ra



제품 특징

- 클램프 강화 공법이 적용된 고출력 LED 투광등
- 150 lm/W 의 높은 광효율
- MH 250 W 대체로 68% 전기료 절감 가능
- 설치각도 제한없이 수직수평 설치 가능
- 다양한 커버렌즈와 설치옵션 선택 가능
- 커버렌즈 적용으로 효율적인 조사각도 조절
- RoHS 규격을 준수한 자외선, 수은 및 납 성분이 없는 친환경 조명

설치장소



특수경계지역



야외체육시설








건물외벽



주유소






커버 옵션

커버					
	확산커버	커버렌즈		리플렉터	
배광곡선					
조사각도	97°	45°	60°	110°	65°

설치 옵션

					
체인	FMB 파이프 브라켓	GS 브라켓	힌지 브라켓	힌지 60도 브라켓	힌지 90도 브라켓

포장 사양

제품 규격 (단위 : mm) · 규격: $\phi 276 \times 277$ mm · 무게: 2.7 kg 	① 단품 박스 (단위 : mm) 	② 팔레트 (단위 : mm) 
--	--	--

타입	단품 박스	팔레트	20피트 컨테이너	팔레트 수량
수량	1	72	720 (10팔레트)	3R x 3R x 8L = 72 (개)
규격(mm)	320 x 320 x 230	1,100 x 1,100 x 1,990	5,500 x 2,200 x 1,990	
총중량(kg)	3.3	263.4	2,634	
CBM	0.024	2.408	24.08	

⚠ 주의사항

- 직류 전원 (DC) 및 안정기에 직접 사용하지 마십시오.
- 밀폐된 곳에 설치하지 마십시오.
- 당사가 제공하는 것 이외에는 설치하지 마십시오.
- 일 권장 작동시간을 준수하여 주십시오.
- 설치 안내서를 반드시 잘 읽고 올바르게 사용해 주십시오.



보증 조건은 품질보증정책을 참조하시고 세부 문의는 영업 담당자와 상의하십시오.

